

UNLIMITED POTENTIAL

GO!

RM 120GO! – THE NEXT LEVEL

Capacity	Up to 385 TPH, depending on material
Inlet opening	46" x 32" 1,160 x 820 mm
Fuel consumption	Approx. 8.5 GPH 34 l/h
Crusher unit	Adjustable speed control, 4-bar impact rotor, direct drive
Feed unit	Asymmetric Hardox 5.2 yd³ vibro feeder Feed control system for automatic crusher load-dependent conveying
Power unit	400 HP John Deere (TIER 4F), 6 cylinders Diesel-electric, 102 kVA 400V gen-set with external outlets for plug-on equipment.
Prescreening	61" x 36" prescreen grizzly with output to main discharge conveyor or via optional side discharge belt
Weight incl. attachment	Approx. 89,500 lbs. 40,700 kg
Screen attachment	12' x 5' single deck mesh screen, 2 sections, includes hydraulic folding return conveyor for 90° stockpiling or recirculating of oversize material (closed circuit). Weight 12,100 lbs. 5,500 kg



Dust Suppression



Magnetic Separator



Hammer Changing Device



RM EXCLUSIVE Release System



FULLY Remote Operated



RM EXCLUSIVE Track and Crush



Engine Compartment Light



RM EXCLUSIVE Factory Direct Training



RM EXCLUSIVE Lifetime Customer Support



25 YEARS OF CRUSHING EXPERIENCE BUILT INTO 1 MACHINE



Superior Material Quality

Simple hydraulic chamber adjustment to meet any spec.



Adjustable Speed Rotor

Multiple rotor speeds to adjust finished product gradation.



Lowest Cost per Ton

Fuel efficient diesel-electric drive burns up to 30% less fuel than comparable impact crushers.



Taking Compact Crushing to the Next Level

Maximum production without sacrificing portability.



Cleaner Finished Product

Optional wind-sifter to remove fabrics and wood-chips from finished material.



High Performance Pre-Screen

Optional active pre-screen available to remove 1 1/8"- material.



Optional Side-Discharge Belt

Segregate fines on the side.

